



### 1-1/4 in. (32 mm) Mini Random Orbital Sanders Unique Features

\* The perfect machine for removing dust nibs and scratches on base coat/clear coat.

\* 1/4-20 Coupling.

\* All sanders come with a 2-3/4 inch grip. 2-1/2 and 3 inch grips are also available. [See Grips.](#)

### 1-1/4 in. (32 mm) Palm-Style Orbital Tool Selector

Standard Product Configuration Table: Mini Random Orbital Sander

Note: 3,000 RPM Machine has planetary gears to reduce speed to 3,000 RPM and 1/4-20 female pad attachment.

RPM	Orbit	Pad Face	Pad Type	Pad P/N	Model No.
3,000	3/32 in. (2.5 mm)	Vinyl for PSA mounted abrasives	1-1/4" (32 mm) diameter	1211500	011000
		Hook for loop mounted abrasives	1-1/4" (32 mm) diameter	1211501	011001
8,000		Vinyl for PSA mounted abrasives	1-1/4" (32 mm) diameter	1211500	011034
		Hook for loop mounted abrasives	1-1/4" (32 mm) diameter	1211501	011035

### 1-1/4 in. (32mm) Random Orbital Sanders Table of Specification

Model Number	Motor		Pad Dim.		* AIR Flow		Product Net Wt.		Height		Length	
	hp	(W)	Inch	(mm)	SCFM	(LPM)	Pound	(kg)	Inch	(mm)	Inch	(mm)
011000	0.28	(209)	1-1/4	(32)	15	(425)	1.24	(0.56)	4.7	(119)	4.9	(124)
011034	0.28	(209)	1-1/4	(32)	15	(425)	1.09	(0.50)	3.9	(99)	4.9	(124)

Additional Specifications: Air Inlet Thread is 1/4" NPT and Hose I.D. is 1/4" (6mm).

\* Air flow/consumption specification are @ 90 psig (6.2 bar)