



32 mm Right Angle Disc Sander

Model No.: AOS-32

Features:

- * Ideal for spot repair on gelcoat and clearcoat paint systems, plus finest sanding of small areas
- * 3 mm (1/8") orbital action minimizes swirl-marks. Tool can be used for both dry and wet applications
- * Tool includes a 32 mm (1-1/2") diameter rubber sanding pad. Optional 19 mm (3/4") diameter rubber pad
- * Uses a powerful 0.4 HP (298 W) air motor for efficient and quick removal of dust nibs and defects
- * Lightweight and easy to use, the perfect combination between power and comfort
- * Rear exhaust to guide air exhaust away from the working places and operator's hand.
- * Useful for Dust Nib Repair on Clearcoat.
- * Random orbital action gives smooth finishes on wood and coated surfaces.
- * Sanding head gives the "random action."
- * Excellent on metal and composites. Ideal for fine sanding.
- * Weighs only 1.4 lbs (0.6 kg) great operator comfort and control.

Specifications:

Air Pressure: 90 PSI

Exhaust: Rear

Air Motor Output: 0.4 HP (298 W)

Speed: 10,000 RPM

Sound Level: 79 dBA

Avg. Air Consumption: 19 SCFM

Hose Size: 3/8"

Orbit Pattern: 3 mm

Pad Size: 1-1/2" / 32mm

Air Inlet Size: 1/4" NPT

Weight: 1.4 lbs / 0.6 kg

Dimensions: 6.22" x 1.61" x 4.13" (158 x 41 x 105)