



Features:

- * Ergonomic grip with overmold.
- * Side handle for added comfort and control.
- * Biased balanced shaft balancers. Balanced with an average weight abrasive and pad.
- * With the air still connected to the tool, the tool can be placed upside down on your work (pad facing upwards).
- * This feature is not to be used for changing the pad.
- * This feature is to be used when the user steps away from the work.
- * Externally mounted hook to hang the tool on the wall.
- * There are common parts between the palm sander and the TwoHAND™ tools.

3 in. (77 mm) TwoHAND™ Geared Buffer/Sander Tool Selector

Standard Product Configuration Table: TwoHAND™ Geared Buffer/Sander – 3,000 RPM				
Pad Face	Vac Type	Pad Type	Pad P/N	Model No.
Vinyl for PSA mounted abrasives	Non-Vac	3"(77 mm) diameter Low Profile	1230100	032400
Hook for loop mounted abrasives	Non-Vac	3"(77 mm) diameter Low Profile	1230101	032401

3 in. (77 mm) TwoHAND™ Random Orbital Sander Tool Selector

Standard Product Configuration Table: TwoHAND™ Random Orbital Sander – 10,000 RPM				
Pad Face	Vac Type	Pad Type	Pad P/N	Model No.
Vinyl for PSA mounted abrasives	Non-Vac	3"(77 mm) diameter Low Profile	1230100	032000
Hook for loop mounted abrasives	Non-Vac	3"(77 mm) diameter Low Profile	1230101	032001

3 in. (77 mm) TwoHAND™ Geared Buffer/Sander/Random Orbital Sander Table of Specifications

Sander Type	* AIR Flow		Pad Dim.		Motor		Product Net Wt.		Length		Air Inlet NPT
	SCFM	(LPM)	Inch	(mm)	hp	(W)	Pound	(kg)	Inch	(mm)	
Non-vacuum	21	(594)	3	(77)	0.46	(343)	2.32	(1.06)	10.04	(255)	1/4"

* Air flow/consumption specification are @ 90 psig (6.2 bar)