











Orbital Sanders Unique Features

- * 1/8 inch (3 mm) orbit for perfect finishes.
- * Compact shape for hard to reach places.
- * [See Back-up Pads-2.](#)
- * All sanders come with a 2-3/4 inch grip. 2-1/2 and 3 inch grips are also available. [See Grips.](#)

3 x 5 in. (81 x 133 mm) Palm-Style Orbital Tool Selector

Standard Product Configuration Table: Orbital Sander – 10,000 RPM – 1/8 in. (3 mm) Orbit

Pad Face	Vac Type	Paper Pattern	Pad P/N	Model No.
Vinyl for PSA mounted abrasives	Non-Vac		1272900	351000
	Central Vac		1272910	351034
	Self-Gen Vac		1272910	351067
Hook for loop mounted abrasives	Non-Vac		1272901	351001
	Central Vac		1272911	351035
			1272942	351036
	Self-Gen Vac		1272911	351068
			1272942	351069

3 x 5 in. (81 x 133 mm) Orbital Sanders Table of Specification

Sander Type	Motor		Nominal Pad Dim.		* AIR Flow		Product Net Wt.		Height		Length	
	hp	(W)	Inch	(mm)	SCFM	(LPM)	Pound	(kg)	Inch	(mm)	Inch	(mm)
Non-Vacuum	0.24	(179)	3 x 5 in. (81 x 133 mm)		17	(481)	1.79	(0.81)	3.7	(95)	6.0	(153)
Central Vacuum	0.24	(179)	3 x 5 in. (81 x 133 mm)		17	(481)	1.89	(0.86)	3.7	(95)	8.5	(217)
Self-Generated Vac	0.24	(179)	3 x 5 in. (81 x 133 mm)		17	(481)	1.93	(0.87)	3.7	(95)	8.8	(224)

Additional Specifications: Air Inlet Thread is 1/4" NPT and Hose I.D. is 1/4" (6mm).
 * Air flow/consumption specification are @ 90 psig (6.2 bar)